



SPECIFICATIONS

Ultra Long Life Lithium-ion Cell

NMC18650-22PL5

Features

- Ultra high lifetime capacity**
- High Specific Power
- High Specific Energy
- High Reliability
- High Safety
- Automotive Class

Applications


- Durable EV, HEV, PHEV
- Durable e-Moped, eBike
- Reliable e-Wheelchair
- Sturdy electrical golf cart
- Power Hobby, Vaping, Mods
- Portable Motorized Medical Equipment
- Long Life High Power Energy Storage System

Specifications*

Nominal Capacity	Discharge at 25 °C at 25 °C, 2.2 A at 25 °C, 11 A	2.1 Ah (Minimum) 2.2 Ah (Typical) 2.4 Ah (Typical)
Lifetime Capacity	Watch chart below	3,950 Ah (Typical)**
Nominal Voltage	Discharge average	3.7 V
Charging	CC-CV, 4.2 V, 44 mA cut-off	0.5C (Standard) 1.0C (Rapid)
Discharging	2.5 V cut-off	11 A (Max. Cont.)
Battery Body Temperature	Charge Discharge Storage	0 ~ 45 °C -20 ~ 60 °C -20 ~ 45 °C
Weight	Average	44.0 g ± 5%


* All test data are averaging with 5 samples obtained from 3 month inventory.
** 2,470 Ah capacity is typically delivered as a power cell; another 1,480 Ah can still be exploited as an energy cell.

Dimensions




For reference only

Discharge Characteristics by Current




Charge: CC/CV, 0.5C/ 4.20 V 44 mA cut-off, Ta = 25 °C
Discharge: CC 1C/5A/ 8A/ 10A/ 11A, 2.50 V cut-off, Ta = 25 °C

Cycle Life Characteristics




Charge: CC/CV, 0.5C/ 4.20 V 44 mA cut-off, Ta = 25 °C
Discharge: CC 1C, 2.75 V cut-off, Ta = 25 °C

Discharge Characteristics by Temperature



Charge: CC/CV, 0.5C/ 4.20 V 44 mA cut-off, Ta = 25 °C
Discharge: CC 0.5C, 2.75 V cut-off, Ta = +55, +25, 0, -10, -20 °C

Charge Characteristics



Charge: CC/CV, 0.5C/ 4.20 V 44 mA cut-off, Ta = 25 °C

The data in this document is for descriptive purposes only and are not intended to make or imply any guarantee or warranty.

To seek more energy storage solutions from AmeriBatt, please email info@ameribatt.com, or visit www.ameribatt.com.